

AMENDMENTS TO THE CLAIMS

Listing of Claims - This will replace all prior listings of claims in the application.

1-6. (Cancelled)

7. (Currently Amended) A ~~computer-implemented~~ method comprising:
identifying_x by a computing device_x a format of a binary file generated by a source application;
selecting_x by the computing device_x a set of user interface display specifications from a plurality of sets of user interface display specifications, based at least in part on the identified format of the binary file; and
processing_x by the computing device_x the binary file to generate a self-contained representation of user interface displays of said binary file rendered when contents of the binary file are viewed using the source application, by associating results of said processing of the binary file with the selected set of user interface display specifications, to enable viewing of the user interface displays ~~without independently of~~ the source application.

8. (Previously Presented) The method of claim 7, further comprising:
attaching by the computing device said self-contained representation with an electronic message; and
transmitting by the computing device said electronic message and said attached self-contained representation to one or more recipients for viewing, where the viewing includes rendering said user interface displays in accordance with said user interface display specifications and user input(s).

9. (Previously Presented) The method of claim 7, wherein said binary file is either a word processing document or a spreadsheet document.

10. (Currently Amended) The method of claim 7, wherein said ~~determining~~
identifying is based upon a filename extension associated with said binary file.

11. (Previously Presented) The method of claim 7, wherein said processing further comprises:

launching by the computing device a locally accessible version of the application;
simulating by the computing device user input(s) to said application based at least in part upon said selected set of user interface display specifications; and
storing by the computing device output(s) from said application in response to said user input(s).

12. (Previously Presented) The method of claim 7, wherein each specification includes one or more transition rules specifying one or more transitions to one or more other user interface displays specified by one or more other specifications.

13. (Previously Presented) The method of claim 12, wherein each transition rule specifies transition to another user interface display specified by another specification when the user interface displays enter a particular user interface display state.

14. (Previously Presented) The method of claim 7, wherein each of said user interface displays comprises one or more display cells, and each of said specification comprises one or more display cell specifications correspondingly specifying the one or more display cells.

15. (Currently Amended) A computer implemented method comprising:

receiving_x by a computing device_x an email message including an associated first attachment of a first attachment type;

determining_x by the computing device_x whether said first attachment type is associated with a member of a group of one or more supported source applications;

selecting_x by the computing device_x a set of one or more user interface display specifications from a plurality of sets of one or more user interface display specifications, based upon said first attachment type if it is determined said first attachment type is associated with a member of said group of one or more supported source applications;

launching_x by the computing device_x a locally accessible version of the associated source application;

simulating_x by the computing device_x one or more user input signals based upon said selected set of one or more user interface display specifications; and

capturing_x by the computing device_x output responses of the associated source application to said one or more user input signals, and associating the captured output responses with the selected set of user interface display specifications to generate a self-contained representation of said first attachment to allow subsequent viewing of the attachment ~~without further use~~independently of the associated source application.

16. (Previously Presented) The method of claim 15, further comprising:

associating by the computing device said representation with said email message in the form a second attachment, replacing said first attachment;

encoding by the computing device said email message and said second attachment; and

transmitting said encoded email message and second attachment to a designated recipient.

17. (Previously Presented) The method of claim 16, wherein said encoding comprises encoding the representation in accordance with the MIME protocol.

18. (Original) The method of claim 15, wherein said first attachment type comprises a proprietary format.

19. (Previously Presented) The method of claim 15, wherein each of said plurality of user interface displays comprises one or more display cells, and each of said user interface display specifications comprises one or more display cell specifications.

20. (Previously Presented) The method of claim 19, wherein each of said specifications further comprises one or more transition rules, each transition rule specifying a transition to a user interface display when the user interface displays enter a particular display state.

21. (Cancelled)

22. (Cancelled)

23. (Cancelled)

24. (Cancelled)

25. (Cancelled)

26. (Cancelled)

27. (Currently Amended) An apparatus comprising:
a storage medium having stored therein a plurality of programming instructions designed to

identify a format of a binary file generated by a source application;

selecting a set of user interface display specifications from a plurality of sets of user interface display specifications, based at least in part on the identified format of the binary file, and

processing the binary file to generate a self-contained representation of user interface displays of said binary file rendered when contents of the

binary file are viewed using the source application, by associating results of said processing of the binary file with the selected set of user interface display specifications to enable viewing of the user interface displays without independently of the source application; and
at least one processor coupled to the storage medium to execute the programming instructions.

28. (Previously Presented) The apparatus of claim 27, wherein the programming instructions are further designed to
attach said self-contained representation with an electronic message; and
transmit said electronic message and said attached self-contained representation to one or more recipients for viewing, where the viewing includes rendering said user interface displays in accordance with said user interface display specifications and user inputs.

29. (Previously Presented) The apparatus of claim 27, wherein said binary file is either a word processing document or a spreadsheet document.

30. (Currently Amended) The apparatus of claim 27, wherein said programming instructions are adapted to perform said determining-identify based upon a filename extension associated with said binary file.

31. (Previously Presented) The apparatus of claim 27, wherein the programming instructions are further designed to
launch a locally accessible version of the application;
simulate user input(s) to said application based at least in part upon said selected set of user interface display specifications; and
store output(s) from said application in response to said user input(s).

32. (Previously Presented) The apparatus of claim 27, wherein each specification includes one or more transition rules specifying one or more transitions to one or more other user interface displays specified by one or more other specifications.

33. (Previously Presented) The apparatus of claim 32, wherein each transition rule specifies transition to another user interface display specified by another specification when the user interface displays enter a particular user interface display states.

34. (Previously Presented) The apparatus of claim 27, wherein each of said user interface displays comprises one or more display cells, and each of said specification comprises one or more display cell specifications correspondingly specifying the one or more display cells.

35. (Currently Amended) An apparatus comprising:

a storage medium having stored therein a plurality of programming instructions designed to

receive an email message including an associated first attachment of a first attachment type,

determine whether said first attachment type is a member of a group of one or more supported source applications,

selecting a set of one or more specifications from a plurality of sets of one or more user interface display specifications, based upon said first attachment type if it is determined said first attachment type is associated with a member of said group of one or more supported source applications,

launch a locally accessible version of the associated source application,

simulate one or more user input signals based upon said selected set of one or more user interface display specifications, and

capture output responses of the associated source application to said one or more user input signals, and associate the captured output responses with the selected set of user interface display specifications to generate a self-

contained representation of said first attachment to allow subsequent viewing of the attachment ~~without further use~~independently of the associated source application; and
at least one processor coupled to the storage medium to execute the programming instructions.

36. (Previously Presented) The apparatus of claim 35, wherein the programming instructions are further designed to

associate said representation with said email message in the form a second attachment replacing said first attachment;

encode said email message and said second attachment; and

transmit said email message and said second attachment to a designated recipient.

37. (Previously Presented) The apparatus of claim 36, wherein said encoding comprises encoding the representation in accordance with the MIME protocol.

38. (Original) The apparatus of claim 35, wherein said first attachment type comprises a proprietary format.

39. (Previously Presented) The apparatus of claim 35, wherein each of said plurality of user interface displays further comprises one or more display cells, and each of said user interface display specifications comprises one or more display cell specifications.

40. (Previously Presented) The apparatus of claim 39, wherein each of said specifications further comprises one or more transition rules, each transition rule specifying a transition to a user interface display when the user interface displays enter a particular display state.